



CSC-9501-2
stainless steel, threaded

1-piece heavy duty ball valve

Threaded ends: NPT

Materials: ASTM A351-CF8M (DIN 1.4408) stainless steel
ASTM A351-CF8 (DIN 1.4308) stainless steel

Pressure Rating: 2000 PSI (PN130)

- stainless steel trim, investment casting body
- standard bore
- silicon-free
- temperature range -60F to 450F
- 15% reinforced glassfibre Teflon seats
- R-PTFE seats
- blow-out proof stem S/S 316
- 100% tested air under water, 100PSI (6 bars), open/close position
- anti-static device
- locking lever

OPTIONS:

- oval handle, butterfly handle
- padlocking device
- polished valve body
- DIN259, DIN2999 threaded ends

DIMENSIONS					
INCH	d	L	C	H	WT
1/2	9.2	66	98	56	0.275
3/4	12.5	70	98	58	0.360
1	15	80	97	70	0.630
1 1/4	20	95	100	74	0.894
1 1/2	25	100	137	74	1.254
2	32	114	141	81	1.852

MATERIALS LIST			
NO	PART NAME	MATERIAL	QTY
1	BODY	CF8M	1
2	INSERT	CF8M	1
3	BALL	316	1
4	SEAT	REIN TEFLON 15% GFT	2
5	BODY SEAL	PTFE	1
6	STEM	AISI316	1
7	THRUST WASHER	PTFE	1
8	STEM PACKING	PTFE	1
9	GLAND WASHER	AISI304	2
10	STEM WASHER	AISI304	1
11	STEM NUT	A2-70	1
12	HANDLE	AISI304	1
13	HANDLE GRIP	PLASTIC	1
14	LOCKING DEVICE	AISI304	1

