



**CSC-9501-2-H**  
stainless steel, threaded

## 1-piece hexagon ball valve

Threaded ends: NPT

Materials: ASTM A351-CF8M (DIN 1.4408) stainless steel  
ASTM A351-CF8 (DIN 1.4308) stainless steel

Pressure Rating: 2000 PSI (PN130)

- stainless steel trim, investment casting body
- standard bore
- silicon-free
- temperature range -60F to 450F
- 15% reinforced glassfibre Teflon seats
- R-PTFE seats
- blow-out proof stem S/S 316
- 100% tested air under water, 100PSI (6 bars), open/close position
- anti-static device

### OPTIONS:

- oval handle, butterfly handle
- 25% reinforced glassfibre Teflon seats
- polished valve body
- DIN259, DIN2999 threaded ends

DIMENSIONS							
INCH	d	B	L	C	H	S	WT
1/4	5	19.5	39	32.5	70	17	0.27
3/8	7	22	44	34.5	70	21	0.27
1/2	9.2	32.5	65	49	90	25	0.27
3/4	12.5	35	70	52	90	32	0.34
1	15	40	80	54	110	38	0.63
1 1/4	20	47.5	95	64	110	48	1.17
1 1/2	25	50	100	68	140	53	1.26
2	32	57	114	75	140	64	2.50

MATERIALS LIST			
NO	PART NAME	MATERIAL	QTY
1	BODY	CF8M	1
2	SEAT RETAINER	CF8M	1
3	BALL	316	1
4	SEAT	REIN TEFLON 15% GFT	2
5	STEM	AISI316	1
6	THRUST WASHER	TEFLON	1
7	STEM PACKING	TEFLON	1
8	THRUST WASHER	AISI304	1
9	STEM WASHER	AISI304	1
10	HANDLE WASHER	AISI304	1
11	STEM NUT	AISI304	1
12	HANDLE	AISI304	1
13	PLASTIC COVER	PLASTIC	1

