



CSC-9503-W
stainless steel, socket weld

3-piece bolted/inline maintenance ball valve

Face to face according to DIN 3203-M3 length

Materials: ASTM A351-CF8M (DIN 1.4408) stainless steel
ASTM A351-CF8 (DIN 1.4308) stainless steel

Pressure Rating: 1000 PSI (PN63)

- full bore
- stainless steel trim
- silicon-free
- high quality investment casting body and caps
- temperature range -60F to 450F
- 15% reinforced glassfibre Teflon seats, in-line repairable
- R-PTFE seats
- adjustable stem packing, blow-out proof stem S/S 316
- 100% tested air under water, 100PSI (6 bars), open/close position
- designed for ISO-5211 mounting flange for actuator

OPTIONS:

- padlocking handle, anti-static device
- actuator mounting bracket
- pneumatic actuator or electric actuator

DIMENSIONS

INCH	B	D	L	C	H	P [†]	Q [†]	WT
1/4	14.2	11.6	60	52	102	42"	M5"	0.45
3/8	17.5	12.7	60	52	102	42"	M5"	0.40
1/2	21.8	15	75	55	116	42"	M5"	0.65
3/4	27.4	20	80	65	116	42"	M5"	0.75
1	34.1	25	90	67.5	150	42"	M5"	1.00
1 1/4	42.7	32	110	77	150	50 [‡]	M6 [‡]	1.70
1 1/2	49.0	38	120	93	187	50 [‡]	M6 [‡]	2.40
2	61.0	49	140	102	187	50 [‡]	M6 [‡]	3.45

[†] ISO 5211 ^{**} F04 [‡] F05

MATERIALS LIST

NO	PART NAME	MATERIAL	QTY
1	BODY	CF8M	1
2	CAP	CF8M	2
3	BALL	316	1
4	SEAT	REIN TEFLON 15% GFT	2
5	STEM	AISI316	1
6	THRUST WASHER	TEFLON	1
7	STEM PACKING	TEFLON	2
8	BOLT	AISI304	4-6
9	HEX NUT	AISI304	4-12
10	BOLT WASHER	AISI304	4-12
11	GLAND NUT	AISI304	1
12	STEM WASHER	AISI304	1
13	STEM NUT	AISI304	1
14	HANDLE	AISI304	1
15	HANDLE COVER	PLASTIC	1
16	BODY SEAL	TEFLON	2
17	LOCKING DEVICE	AISI304	1

